

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L1	0	(418/201.1,201.3,206.1) and (gear or screw) and (gap or clearance)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2004/11/22 13:43
L2	446	((418/201.1,201.3,206.1).ccls.) and (gear or screw) and (gap or clearance)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2004/11/22 12:14
L3	5	("3073513" "3975123" "4993930" "5037282").PN.	US-PGPUB; USPAT; USOCR	OR	ON	2004/11/22 12:26
L4	9	("0885109" "2325617" "2349022" "2362106" "3918838").PN.	US-PGPUB; USPAT; USOCR	OR	ON	2004/11/22 13:02
L5	31	((418/189,190).ccls.) and (gear or screw) and (gap or clearance) and depth	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2004/11/22 13:39
L6	0	(418/201.1,201.3,206.1) and (gear or screw) and (gap or clearance) and depth	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2004/11/22 13:43
L7	79	((418/201.1,201.3,206.1).ccls.) and (gear or screw) and (gap or clearance) and depth	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2004/11/22 13:54
L8	137	((gear or screw) adj3 compressor) and (gap or clearance) and depth	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2004/11/22 13:54
L9	53	((gear or screw) adj3 compressor) and ((gap or clearance) near4 rotor) and depth	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2004/11/22 13:54